## IN THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

## **Listing of Claims:**

1. (currently amended) A television receiver that inputs encoded picture data that contains motion information used when the picture data were was encoded and moving picture data that does not contain the motion information, the television receiver comprising:

decoding means for decoding the encoded picture data according to the motion information and <u>for</u> outputting the decoded picture data;

picture process means for performing a motion adaptive picture process for on the decoded picture data and for outputting the processed data to a display section; and

time axis compensation means for supplying motion information according to the generated decoded picture data to the picture process means in synchronization with timing of which the supply of the decoded picture data are supplied to the picture process means,

wherein the picture process means performs a picture process on the decoded picture data according to the motion information supplied from the time axis compensation means.

2.	(currently amended) The television receiver as set forth in claim 1,
	—wherein
	the encoded picture data contains difference data against a reference picture, and
	wherein the decoding means adds past or future picture data generated according
to the motio	n information and the difference data to generate the decoded picture data.
3.	(currently amended) The television receiver as set forth in claim 1,
	—wherein
	the motion information is a moving vector detected for each macro block
composed o	f a plurality of pixels, and
	wherein-the picture process means references the moving vector for each macro
block and pe	erforms the motion adaptive picture process.

4. (currently amended) The television receiver as set forth in claim 1,

Application No.: Not Yet Assigned

Docket No.: SONYJP 3.3-391

wherein when the motion information supplied from the time axis compensation means exceeds a predetermined value, the picture process means performs a moving picture adaptive process foron the picture data and when the supplied-motion information supplied from the time axis compensation means is less than or equal to or smaller than the predetermined value, the picture process means performs a still picture adaptive process foron the picture data.

- 5. (currently amended) The television receiver as set forth in claim 1,

  —————wherein the picture process means is a noise reduction circuit that adds picture
  data of successive frames to the decoded picture data at a predetermined ratio-only when the
  supplied motion information is equal to or smaller than the predetermined value according to the
  motion information supplied from the time axis compensation means.
- 6. (currently amended) The television receiver as set forth in claim 1, further comprising:

motion detection means for inputting the moving picture data that do not contain motion information, detecting motion information of the moving picture data, and supplying the detected motion information to the picture process means; and,

selection means for supplying one of output picture data of the decoding means and picture data that do not contain the motion information to the picture process means.

wherein when the moving picture data are input to the motion detection means, the picture process means performs the motiona picture adaptive process on the moving picture data according to the detected motion information-detected by the motion detection means.

7.	(currently amended) The television receiver as set forth in claim 1,	
	-wherein	
	_the encoded picture data areis an elementary stream according to the MPEG2	
system, and		
	the time axis compensation means supplies the motion information to the picture	
process mean	s in synchronization with the supply of the decoded picture data to the picture	
process mean	s according to encoding mode information representing the type of the encoded	
picture data supplied together with the motion information from the decoding means.		

8. (currently amended) A picture processing method of inputting encoded picture data that contains motion information used when the picture data were was encoded and moving picture data that does not contain the motion information, and performing a predetermined picture process, the method comprising the steps of:

decoding the encoded picture data according to the motion information and outputting the decoded picture data supplying the decoded picture data to a processor;

performing a motion adaptive picture process for the decoded picture data; and supplying motion information according to the generated decoded picture data to the picture process stepprocessor in synchronization with timing of which the supply of the decoded picture data are supplied to the picture process step, processor; and

\_\_\_\_\_\_ performing a picture process on the decoded picture data or the moving picture data,

wherein when the decoded picture data is supplied to the processor, the picture process step performs a picture process is performed on the decoded picture data according to the motion information supplied from the time axis compensation stepto the processor.

- 9. (cancelled)
- 10. (cancelled)
- 11. (cancelled)
- 12. (cancelled)
- 13. (currently amended) The picture processing method as set forth in claim 8, further comprising the steps of:

inputting the moving picture data, that do not contain motion information. detecting motion information of the moving picture data, and supplying the detected motion information to the picture process step; and processor,

supplying one of output picture data of the decoding step and picture data that do not contain the motion information to the picture process step.

wherein when the picture data are input to the motion detection step, the picture process performing step performs the motion a picture adaptive process on the moving picture data according to the detected motion information detected by the motion detection step supplied to the processor.

- 15. (new) The television receiver as set forth in claim 6, wherein the picture process means is a noise reduction circuit that adds picture data of successive frames to the decoded picture data at a predetermined ratio when the motion information supplied from the time axis compensation means or the detected motion information is less than or equal to a predetermined value.
- 16. (new) The television receiving as set forth in claim 6, further comprising:
  an operation section that selects a channel in which a broadcast signal modulated
  as the encoded picture data has been received or a channel in which a broadcast signal
  demodulated as the moving picture data has been received;

selection means for supplying the decoded picture data or the non-encoded picture data to the picture process means; and

control means for controlling the selection means according to channel information selected by the operation section.

17. (new) The picture processing method as set forth in claim 13, wherein the picture process is a noise reduction process that adds picture data of successive frames at a

predetermined ratio when the motion information supplied to the processor is less than or equal to a predetermined value.

18. (new) The picture processing method as set forth in claim 8, wherein the picture process is a noise reduction process that adds picture data of successive frames to the decoded picture data at a predetermined ratio according to the motion information supplied to the processor.